# ICON Vehicle Dynamics 59706CP Installation Instructions

S2 Secondary 2.5 RR CDCV Shock Pair for Toyota 4Runner & Tacoma

Part number: 59706CP

trailfortress.com/icon-vehicle-dynamics-toyota-s2-secondary-2-5-rr-cdcv-pair-59706cp

Scan for fitment, price and install help

ICON VEHICLE DYNAMICS ™
7929 Lincoln Ave. Riverside, CA 92504
Phone: 951.689.ICON Fax: 951.689.1016

# 59706CP INSTALLATION INSTRUCTIONS

*9-3-2015 REV.A*

| PART # | DESCRIPTION |
|---|---|
| 59706CP | TOYOTA S2 SECONDARY 2.5 VS RR CDCV PAIR |

## COMPONENTS INCLUDED

| | |
|---|---|
| (1) 154962CD TOYOTA S2 RR CDCV SECONDARY (DRVR)<br>(1) 154962CP TOYOTA S2 RR CDCV SECONDARY (PASS) | (1) 59706H TOYOTA S2 HARDWARE KIT |

## HARDWARE INCLUDED

59706H HARDWARE KIT

| | |
|---|---|
| (2) 250002 7.50 UNIVERSAL RESI MT PLATE<br>(2) 605101 3/8-16 X 1.000 BOLT<br>(2) 605122 3/8-16 C-LOCK NUT | (4) 605133 3/8 SAE FLAT WASHER<br>(4) 605926-BLK 5-1/2 X 0.14 NYLON CABLE TIE<br>(1) 611051 #40 2 1/16-3" HOSE CLAMP KIT |

611051 HARDWARE KIT

| | |
|---|---|
| (4) 605931 1/2 X 2 1/16 - 3" ID #40 SS HOSE CLAMP | |

## TOOLS REQUIRED

| | |
|---|---|
| 3/4" SOCKET / WRENCH | 9/16" SOCKET / WRENCH |

## TECH NOTES

*1. REQUIRES USE OF ICON S2 SHOCK HOOP KIT (56102).*

*2. YOUR ICON SHOCK ASSEMBLIES COME FACTORY CHARGED TO 150 PSI. RELEASING NITROGEN PRESSURE MAY LEAD TO SHOCK MALFUNCTION AND REDUCED RIDE QUALITY. FAILURE CAUSED BY LOW NITROGEN PRESSURE IS NOT COVERED UNDER ICON'S WARRANTY POLICY.*



**WARNING!**

*** READ ALL INSTRUCTIONS THOROUGHLY FROM START TO FINISH BEFORE BEGINNING INSTALLATION! IF THESE INSTRUCTIONS ARE NOT PROPERLY FOLLOWED SEVERE FRAME, SUSPENSION AND TIRE DAMAGE MAY RESULT TO THE VEHICLE!*

*** ICON VEHICLE DYNAMICS RECOMMENDS THAT YOU EXERCISE EXTREME CAUTION WHEN WORKING UNDER A VEHICLE THAT IS SUPPORTED WITH JACK STANDS.*

*** ICON VEHICLE DYNAMICS RECOMMENDS ALL INSTALLTION TO BE PERFORMED BY A PROFESSIONAL SHOP/SERVICE TECHNICIAN. PRODUCT FAILURE CAUSED BY IMPROPER INSTALLATION WILL NOT BE COVERED UNDER ICON'S WARRANTY POLICY.*

## INSTALLATION

**REFER TO ICON (56102) 07-UP FJ/03-UP 4RUNNER/05-UP TACOMA S2 SHOCK HOOP KIT FOR FULL INSTALLATION INSTRUCTIONS.**






trailfortress.com/icon-vehicle-dynamics-toyota-s2-secondary-2-5-rr-cdcv-pair-59706cp

# 2.5 VS SERIES SHOCK & COILOVER TECHNICAL INFORMATION

## MAINTENANCE

ICON shock absorbers are a high quality rebuildable race style shock absorber designed for optimal performance. With a unit of this caliber on your vehicle, routine maintenance is required to keep them looking and operating in like new condition. Residual oil and assembly lube may be present at all seal paths from the factory out of the box and is considered normal. Pooling of oil however is not acceptable at any time and one should contact the iCON dealer where purchased.

***BELOW ARE GUIDELINES BASED ON HOW YOU USE YOUR VEHICLE BUT YOUR MILEAGE MAY VARY:***

***STREET USE:***

- Send in for factory servicing every 40,000 miles or if a leak develops, ride quality decreases, or they begin to make excessive noise.
- Remove any buildup of road salt, mud, or debris from shocks and coil springs anytime accrued
- Clean with mild soap and water with each oil change or anytime you notice build up.
- Wax the cylinders yearly with automotive wax to prevent corrosion.
- Check nitrogen pressure yearly. (252004 charge needle assembly available at any ICON distributor)
- Check bearings for excessive wear yearly.
- **DO NOT** apply any type of lube to the upper and lower bearings.

***STREET/DIRT:***

- Send in for factory servicing every 15,000 miles or if a leak develops, ride quality decreases, or they begin to make excessive noise.
- Clean with mild soap and water with each oil change, offroad trip, or anytime you notice build up.
- Wax the cylinders yearly with automotive wax to prevent corrosion.
- Check nitrogen pressure each dirt outing. (252004 charge needle assembly available at any ICON distributor)
- Check bearings for excessive wear yearly.
- **DO NOT** apply any type of lube to the upper and lower bearings.

***DIRT USE:***

- Send in for factory servicing every 1,000 miles.
- Check nitrogen pressure each outing. (252004 charge needle assembly available at any ICON distributor)
- Remove any buildup of mud or debris from shocks and coil springs after every outing.

***SELF-SERVICE:***

- Contact ICON for service kits & tools at (951) 689-4266.

## PRODUCT REGISTRATION

Please visit: http://www.iconvehicledynamics.com/tech-support/registration/ to register your product.

## ICON VEHICLE DYNAMICS SHOCK ABSORBER WARRANTY

This shock absorber has a 1 year warranty against any manufacturer's defects. If a shock fails within the initial year of ownership, the shock must be shipped to ICON Vehicle Dynamics for inspection and service. If a shock is inspected and it has been determined the shock failed due to neglect, damage caused by improper installation or any other reason besides "normal wear and tear", the owner of said shock is responsible for all service costs. This includes labor, parts, and shipping.

ICON Vehicle Dynamics warrants to the original retail purchaser who owns the vehicle on which the product was originally installed. ICON Vehicle Dynamics does not warrant the product for finish, alterations, modifications and/or installation contrary to ICON Vehicle Dynamics instructions. ICON Vehicle Dynamics products are not designed, nor are they intended to be installed on vehicles used in race applications, for racing purposes or for similar activities. (A "race" is defined as any contest between two or more vehicles, or a contest of one or more vehicles against the clock, whether or not such contest is for a prize). This warranty does not include coverage for police or taxi vehicles, race vehicles, or vehicles used for government or commercial purposes. Also excluded from this warranty are sales outside of the United States of America and Canada.

ICON Vehicle Dynamics' obligation under this warranty is limited to the repair or replacement, at ICON Vehicle Dynamics' discretion, of the defective product. Any and all costs of removal, installation or re-installation, freight charges and incidental or consequential damages are expressly excluded from this warranty. Items that are subject to wear are not considered defective when worn and are not covered.

ICON Vehicle Dynamics components must be installed as a complete kit as shown in our current application guide. Any substitutions or exemptions of required components will immediately void the warranty. Some finish damage may happen to parts during shipping and is not covered under warranty.

This warranty is expressly in lieu of all other warranties expressed or implied. This warranty shall not apply to any product that has been improperly installed, modified or customized subject to accident, negligence, abuse or misuse.

To send a shock in for warranty please visit our website http://www.iconvehicledynamics.com/tech-support/shock-service/

ICON VEHICLE DYNAMICS
PERFORMANCE SUSPENSION SYSTEMS AND SHOCK ABSORBERS

7929 Lincoln Ave. Riverside, CA 92504 Phone: 951.689.ICON Fax: 951.689.1016
www.iconvehicledynamics.com

FOLLOW US ON FACEBOOK!



trailfortress.com/icon-vehicle-dynamics-toyota-s2-secondary-2-5-rr-cdcv-pair-59706cp